

TORSION TRIP-EDGE SPECIFICATIONS

MODEL	LENGTH OVERALL	HEIGHT w/6" C.E.	VERTICAL RIBS	SEMI CIRCLE	BOTTOM ANGLE	CUTTING EDGE	MOLDBOARD THICKNESS
TTPY10PA45	10'	44"	10	3-1/2" x 3-1/2" x 1/2"	4" x 4" x 5/8"	5/8" x 6"	3/8" POLYMER
TTPY11PA45	11'	44"	10	3-1/2" x 3-1/2" x 1/2"	4" x 4" x 5/8"	5/8" x 6"	3/8" POLYMER



STANDARD FEATURES

- One piece polymer sheet
- Moldboard extends over cutting edge
- Two 3" double acting reverse cylinders
- 92" Push table has four pin connection
- Vertical ribs 3" @ top, 4-1/2" @ bottom
- Top angle reinforcement

OPTIONAL ACCESSORIES

- Adjustable caster assemblies
- Adjustable runner assemblies
- Adjustable Pneumatic tires
- Cutting edge shoes
- Curb guards
- Cushion Valve
- Quick link swivel bar
- Rubber cutting edge
- Carbide cutting edge
- Tapered rubber deflector

- One piece AASHO cutting edge
- 3/4" Wire torsion springs
- Springs clamped and adjustable
- "A" frame triangular weldment
- Oscillating captured swivel bar
- 30-1/2" pin center swivel bar

Serviced and Sold by:

Manufactured by: Flink Company
502 N. Vermillion Street
Streator, Ill 61364

Phone • 815/673-4321
Fax • 815/672-2678
Email • flink@sainet.net

Specifications Subject to Change Without Notice